


Type:	BURRY-DAC-G	REV: 2.1
Issued:	31/07/2018	PB
Modified:	29/12/2020	KP

Direct buried single jacket central loose tube drop cable with FRP and glass yarn strength members BURRY-DAC-G



*schematic drawing, not to scale

APPLICATION:

Optical access cable with glass yarns reinforcement
Direct buried design
Fully dielectric cable
Last mile connection
High crush resistance
Installation into existing ducts or direct buried

STRUCTURE AND COMPOSITION:

Central loose tube (PBT) with filling compound
Up to 24 optical fibres (250 µm)
Fiberglass yarns as strain relief and water absorbent
Embedded FRP strength members
Highly resistant outer jacket made of hard polyolefin material,
UV resistant

DESIGNS:

Variant	Quantity [pcs]		Ø nominal (±0,4) [mm]	Nominal weight (±5%) [kg/km]
	Fibres total	Fibres per tube		
1T x 2-12F	2-12	2-12	6,0	29
1T x 14-24F	14-24	14-24	6,5	36

TECHNICAL AND ENVIRONMENTAL CABLE CHARACTERISTICS

Max short term tensile load	IEC 60794-1-21 E1, $\epsilon < 0,6\%$, $\Delta\alpha \leq 0,05$ dB/km (reversible)	1000 N
Max long term tensile load	IEC 60794-1-21 E1, $\epsilon \leq 0,05\%$, $\Delta\alpha \leq 0,05$ dB/km	210 N
Crush performance	IEC 60794-1-21 E3, 1min, $\Delta\alpha \leq 0,1$ dB, no significant sheath damage	4000 N/10cm
Impact	IEC 60794-1-21 E4, R=300[mm], 3 times, distance ≥ 500 [mm], $\Delta\alpha \leq 0,05$ dB	10J
Bending performance	IEC 60794-1-21 E6, 50[N], 20 cycles, $\Delta\alpha \leq 0,05$ dB	10 x D
Torsion	IEC 60794-1-21 E7, ± 180 [°], 20 cycles, $\Delta\alpha \leq 0,05$ dB	50N
Temperature range		
Installation		-15... +55 °C
Operation	IEC 60794-1-22 F1, $\Delta\alpha \leq 0,05$ dB/km	-40... +70 °C
Transport & Storage		-40... +70 °C
Water penetration	IEC 60794-1-22 F5, 1[m] head, 24[h], no leakage	3m sample

(*) values for single-mode fibres, all optical measurements performed at 1550nm

OPTICAL FIBRES AND LOOSE TUBES COLOUR IDENTIFICATION

For optical fibres and loose tubes identification information please see **DSH_Colors_CODE_XXXX** document.

FIBRES PARAMETERS

For selected post-production optical fibres parameters please see **DSH_OFFP** document.

MARKING

The following print (black inkjet or other suitable method) is applied at 1-meter intervals:

- Supplier: FIBRAIN
- Standard code (Product type, fibre type, fibre count)
- Year of manufacture: xxxx
- Length marking in meters
- Cable ID / Drum No

Example: FIBRAIN BURRY DAC-G 2F SM G657A1 FTTH ACCESS CABLE "YEAR OF MANUFACTURE" "LASER SYMBOL" "LENGTH MARKING" "BATCH NUMBER"

The accuracy of marking is $\pm 1\%$. Remarketing is in accordance with Bellcore GR 20 and supersedes earlier markings. Occasional loss of marking is possible. Cables can be supplied with a range of single mode or multimode fibres and customized print.

Type:	BURRY-DAC-G	REV: 2.1
Issued:	31/07/2018	PB
Modified:	29/12/2020	KP

PACKAGING

Cables will be shipped on disposable wooden or treated wooden drums. Both ends of the cable will be capped and accessible for testing. Rotation direction arrow will be marked on the drum together with identification information.

DELIVERY LENGTH

2000 – 8000 meters \pm 5%, with possibility of supplying up to 5% of total contract quantity as short length cables which should be above 1000 meters long. Tolerance of 5 % of order quantity shall be allowed.

This document and the statements contained in it are not intended for customers within the meaning of the Civil Code. The information submitted in this document is to our knowledge and belief true at the time of issue, however, we do not assume any liability whatsoever for its accuracy, and completeness. This document is for informational purposes on an "as is" basis only and Fibrain reserves the right to change its contents at any time without prior notice. The specification cannot, in any case, be considered an offer within the meaning of the Civil Code and is not contractually valid unless specifically authorized by Fibrain. Before using this product, its buyer and/or user has to make sure that it is suitable for the intended use. All liability issues related to this product are subjected to the seller's separate Terms of Sale or the terms and conditions agreed with the Fibrain representative or distributor.